

Cyclopital3D



Wide-Angle Lens for the Sony PMW-TD300



What's in the package:

- | | |
|---------------------------|-----------------------|
| 1 Wide-angle lens | 1 95mm Front lens cap |
| 1 Century Optics Sunshade | 1 Rear lens cover |

Cyclopital3D Sony PMW-TD300 Wide-Angle Lens

Having the ability to capture a wider field of view in a scene can often make the difference of whether a shoot is successful or not. The Cyclopital3D Wide-angle Lens (WAL) four-piece set expands the capabilities of your Sony TD300 Camcorder by widening the field of View from 47.8 degrees (40.6mm EQFL) to 80 degrees (21.5mm EQFL).

The WAL set includes a Century Optics Sunshade, which accepts the Century Optics 4x4 professional grade filter holder, item #OVS-FF44-00 from B & H Photo.

The Cyclopital3D Wide-angle lens incorporates high-quality, 3-element optics that are fully coated and corrected. These lenses produce bright, high-contrast images with no vignetting, and very little distortion or chromatic aberration.

Features and Benefits:

- Expands camera's field of view from 47.8 degrees to 80 degrees; 35mm EQFL from 40.6mm to 21.5mm
- Full zoom-through capability
- Incorporates 3-element lenses
- Includes Century Optics Sunshade which also accepts the Century Optics 4x4 pro filter holder item #OVS-FF44-00 from B & H Photo.
- Easy thumb-screw attachment after first use
- Includes custom rear lens cover and front lens cap

Installation Instructions:

- To attach the WAL you must first remove the front bezel from the camera by unscrewing the four small screws using a cross-point screwdriver. The camera bezel screws can be stored in the threaded holes in the WAL back cover or in the threaded holes in the back side of the WAL.
- Attach the WAL to camera with the word “Cyclopital3D” on the top using the four new thumb-screws provided. Do not over-tighten the screws- finger tightening is sufficient and the use of tools is not necessary.



Tips for use:

- Full zoom through capability. With the WAL attached the zoom range of the camera becomes 21.5mm to 157mm. The lens can be used at any zoom setting.

Care and Maintenance:

- If you drop the Wide-angle Lens it will break. Please treat it with the same care you would give to any expensive camera lens. If the unit sustains impact damage it may be possible to repair it using super glue (cyanoacrylate), which bonds well to the composite material used in its construction.
- In the unusual case that the internal glass of the lenses gets dirty, the unit can be disassembled and cleaned by someone skilled in working with delicate optical devices. If you are in doubt of your capabilities, Cyclopital3D can clean the unit for a small fee.

Warranty

Your adapter comes with a Limited Warranty against defects in workmanship and materials for 30 days from the date of purchase. The limited warranty does not apply if the product has been damaged by accident, mishandling, misuse, abuse, or alteration.